



RAVENOL VolISynth Turbo VST SAE 5W-40



1L | 1111136-001
4L | 1111136-004
5L | 1111136-005
10L | 1111136-010
20L | 1111136-020
20L | 1111136-B20
60L | 1111136-060
60L | 1111136-D60
208L | 1111136-208
208L | 1111136-D28
1000L | 1111136-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111136

Viscosity: 5W-40

Specification: ACEA A3/B4, API CF, API SN

Oil type: Full synthetic

Approvals: API SN, BMW Longlife-01, MB-Freigabe 229.5, Renault RN0700/RN0710, VW 502 00, VW 505 00

Recommendation: Chrysler MS-10725, Chrysler MS-10850, Chrysler MS-12991 (MS-10896), Fiat 9.55535-Z2, MB 226.5, MB 229.3, Opel/GM-LL-B-025, Porsche A40, PSA B71 2296

Application: Passenger car

Technology: Clean Synto®, USVO®

RAVENOL VolISynth Turbo VST SAE 5W-40 is a PAO (Polyalphaolefin) based, full synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

RAVENOL VolISynth Turbo VST SAE 5W-40 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

RAVENOL VolISynth Turbo VST SAE 5W-40 guarantees operational safety concerning all driving conditions as for example regarding extreme stop and go traffic as well as high speed drives on motorways.

Extended oil change intervals according to the manufacturer's instructions.

Application Note

RAVENOL VolISynth Turbo VST SAE 5W-40 is suitable for the energy saving operation all the year of all modern cars with petrol and diesel engines in passenger cars, vans, small transporters and similar vehicles and was specially developed for turbo chargers as well as the catalytic operation.

Characteristics

- High abrasion resistance.

- Fuel saving because of easy running characteristics.
- Excellent detergent and dispersant characteristics.
- Prevention of black sludge creation.
- Long endurance because of high oxidation stability.
- Excellent cold start performance.
- Very good viscosity temperature behaviour.
- Low evaporation.
- Suitable for catalysts.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	848,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	13,9	DIN 51562-1
Viscosity at 40 °C	mm ² /s	82,5	DIN 51562-1
Viscosity Index VI		174	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,9	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	4700	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	13.900	ASTM D4684
Pourpoint	°C	-51	DIN ISO 3016
Noack Volatility	% M/M	7,3	ASTM D5800
Flashpoint	°C	236	DIN EN ISO 2592
tbn	mg KOH/g	10,5	ASTM D2896
Sulphated Ash	%wt.	1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

28.05.2023