



# RAVENOL Oldtimer 70-er SAE 20W-50 API SE

**Kategorie:** Oldtimer engine oil (Classic products)

**Artikelnummer:** 1119116

**Viscosity:** 20W-50

**Specification:** API SE

**Oil type:** Mineral

**Application:** Oldtimer



1L | 1119116-001

5L | 1119116-005

5L | 1119116-005

20L | 1119116-020

20L | 1119116-B20

60L | 1119116-060

60L | 1119116-D60

With their unique formulation, **RAVENOL Classic 2 Engine Oils** extend the service life of engines in older vehicles by offering protection against sludge formation and wear and tear. By minimising friction, fuel consumption is also reduced. Optimal cold-start performance.

**RAVENOL Oldtimer 70-er SAE 20W-50 API SE** is an alloyed multi-grade engine oil designed for use in classic vehicles built prior to 1979. It is manufactured using carefully selected pure mineral raffinates and additives. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol and diesel engines / classic vehicles built before 1979. Using this oil in modern engines can lead to defective performance or cause damage.

## Application Note

**RAVENOL Oldtimer 70-er SAE 20W-50 API SE** is designed for use in the engines of vehicles which were built prior to 1979, where the API specification SE is required.

Observe the oil change intervals specified in the manufacturer's instructions.

## Characteristics

- Corrosion protection
- Good shear stability
- Good oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety also at boundary lubrication conditions
- Neutrality towards sealing materials
- Very good cold start characteristics
- Prevents the formation of adhesions, varnish, carbon deposits and sludging (black sludge) on cylinders, pistons, valves, spark plugs and in turbochargers

# Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	879,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm²/s	18,6	DIN 51562-1
Viscosity at 40 °C	mm²/s	171,6	DIN 51562-1
Viscosity Index VI		122	DIN ISO 2909
Pourpoint	°C	-27	DIN ISO 3016
Flashpoint	°C	252	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**  
29.05.2023