

RAVENOL ATF BTR 95LE

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211116

Oil type: Synthetic

Recommendation: ATF Type TQ95, M74LE, M85LE, M91LE, M95LE

Application: Passenger car



RAVENOL ATF BTR 95LE is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF BTR 95LE is an ATF (Automatic transmission fluid) for modern automatic transmission of BTR Engineering Australia. Guarantees maximum wear protection in all operating conditions.

RAVENOL ATF BTR 95LE is red colored.

Application Note

RAVENOL ATF BTR 95LE is for use in automatic transmission of BTR Engineering Australien for SsangYong Musso, Korando, Rexton, Aktyon, FORD Falcon, Fairlane, LTD, Maserati Quattroporte, 3200GT, Mitsubishi VF Nimbus, KF Verada and others. Under normal operating conditions maintenance-free filling.

Characteristics

- Superior resistance against lubricant failure under harsh operating conditions
- Longer oil life, longer life of the transmission allows longer change intervals
- Outstanding resistance against sludge and deposit formation
- Excellent oxidation resistance and thermal stability
- Superior wear protection, better foaming resistance for smoother shifting and less wear on bearings, bushings and gears
- Excellent fluidity at low temperatures
- More consistent switching performance and optimized frictional properties
- Prevention of coupling loops in modulation rotary converters
- Longer life of oil and clutch allows soft switching at low temperatures
- Improved shear stability

1L | 1211116-001

4L | 1211116-004

10L | 1211116-010

20L | 1211116-020

20L | 1211116-B20

60L | 1211116-060

60L | 1211116-D60

208L | 1211116-208

208L | 1211116-D28

1000L | 1211116-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	847,0	EN ISO 12185
Colour		rot	VISUELL
Pourpoint	°C	-54	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

30.05.2023