



RAVENOL Getriebeoel TSG SAE 75W-90



1L | 1222101-001

4L | 1222101-004

10L | 1222101-010

20L | 1222101-020

20L | 1222101-B20

60L | 1222101-060

60L | 1222101-D60

208L | 1222101-208

208L | 1222101-D28

1000L | 1222101-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222101

Viscosity: 75W-90

Specification: API GL-4

Oil type: Synthetic

Recommendation: Ford M2C-175, Opel/GM B0401043, VW 501 50, VW G 052 911 A2, VW G 060 726 A2

Application: Passenger car, Truck

RAVENOL Getriebeoel TSG SAE 75W-90 is a synthetic multi-purpose transmission oil for maximum duty manual transmissions.

RAVENOL Getriebeoel TSG SAE 75W-90 is designed based on high-quality synthetic base oils with special additive treatment and inhibition coordinated to the increased stress on manual transmission oils and ensuring trouble-free transmission function.

Application Note

RAVENOL Getriebeoel TSG SAE 75W-90 is suitable for highly stressed manual transmissions (with and without synchronising), transfer cases and steering gearboxes in vehicles and work machines.

Characteristics

- excellent ageing resistance
- extra high pressure absorption properties
- optimal viscosity-temperature properties
- excellent low temperature properties
- shearing stability
- stable lubricating film even under high stress
- extremely low pour point
- good elastomer compatibility to prevent leaks

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	862,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm²/s	16,5	DIN 51562-1
Viscosity at 40 °C	mm²/s	111,7	DIN 51562-1
Viscosity Index VI		160	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	99.700	ASTM D2983
Pourpoint	°C	-48	DIN ISO 3016
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.
30.05.2023