



RAVENOL Getriebeöl LS SAE 75W-90



Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222102

Viscosity: 75W-90

Specification: API GL-5 + LS, MIL-L-2105 D

Oil type: Synthetic

Recommendation: GM 1940058, GM 88862624, GM 88862625, GM 93165388, ZF TE-ML 05C, ZF TE-ML 05D

Application: Passenger car, Truck

RAVENOL Getriebeöl LS SAE 75W-90 is a synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeöl LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

1L | 1222102-001

4L | 1222102-004

10L | 1222102-010

20L | 1222102-020

20L | 1222102-B20

60L | 1222102-060

60L | 1222102-D60

208L | 1222102-208

208L | 1222102-D28

1000L | 1222102-700

Application Note

RAVENOL Getriebeöl LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

Characteristics

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	870,0	EN ISO 12185
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	17,1	DIN 51562-1
Viscosity at 40 °C	mm ² /s	118,3	DIN 51562-1
Viscosity Index VI		158	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	88.800	ASTM D2983
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	192	DIN EN ISO 2592
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

30.05.2023