



RAVENOL Hot Red Grease HRG 3

Kategorie: Grease

Artikelnummer: 1340122

Specification: DIN 51502: KP3P-25, ISO 6743-9: ISO-L-XBEEB3

Application: Passenger car, Truck, Industry



RAVENOL Hot Red Grease HRG 3 is a red lithium complex soap lubricating grease on the basis of high quality base oils. Excellent work resistance, rust and corrosion protection. Application for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures. Particularly recommended for the lubrication of wheel bearings on commercial vehicles and for high-speed passenger car wheel bearings.

Application Note

RAVENOL Hot Red Grease HRG 3 is used for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures.

RAVENOL Hot Red Grease HRG 3 is particularly recommended for the lubrication of commercial vehicles and for high-speed passenger car wheel bearings.

0.4L | 1340122-400

1L | 1340122-001

5L | 1340122-005

10L | 1340122-010

15L | 1340122-015

25L | 1340122-025

180L | 1340122-180

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		rot	VISUELL
Thickener		Lithium-Komplekseifen	DIN 51757
NLGI-Class		3	DIN 51818
Product Classification		KP3P-25	DIN 51502
Working Temperature	°C	-25 / +160	DIN 51825
Short term temperature up to	°C	200	DIN 51757
Worked Penetration at 60 Strokes	mm/10/25°C	220-250	ISO 2137
Corrosion (SKF Emscor dist. Water)	Korr. Grad	0	DIN 51802
Dropping Point	°C	>260	DIN ISO 2176
Copper Corrosion (24h/120 °C)		1	DIN 51811
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
VKA Pressure Carrying Capacity	N	2600 - 2800	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	mm²/s	150	DIN 51562-1

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

31.05.2023