



5L | 1350350-005 10L | 1350350-010 20L | 1350350-020 20L | 1350350-B20 60L | 1350350-060 208L | 1350350-208

## **RAVENOL Bohroel-Konzentrat SH**

Kategorie: Industrial oil
Artikelnummer: 1350350
Oil type: Semi-synthetic
Application: Industry

**RAVENOL Bohroel-Konzentrat SH** is a semi-synthetic universally applicable water-miscible cooling lubricant suitable for a wide range of applications in the field of metal cutting (steel, cast iron, light and non-ferrous metals.

**RAVENOL Bohroel-Konzentrat SH** enables long service lives as well as clean surfaces of the workpieces.

**RAVENOL Bohroel-Konzentrat SH** is free from boric acid, chlorine, sec. amines and formaldehyde.

## **Application Note**

**RAVENOL Bohroel-Konzentrat SH** is used as an emulsion for general cutting applications (boring, turning, milling), also for increased requirements such as broaching, sawing, grinding and thread cutting.

**RAVENOL Bohroel-Konzentrat SH** is used for processing any material without restrictions. Also suitable for grinding operations.

**Application concentrations (mixing ratio):** 

RAVENOL Bohroel-Konzentrat SH can be used as follows

- > for grinding: approx. 2.5 % concentrate (1:40)
- > for turning, drilling, milling: approx. 5 % concentrate (1:20)
- > for noncutting forming: approx. 10 % concentrate (1:10)

Refractometer multiplier: 1.7

**RAVENOL Bohroel-Konzentrat SH** is stirred into water in the appropriate mixing ratio. It is recommended to use a mixer and to check the concentration regularly.

Check material compatibility before use and watch out for discoloration!

## **Characteristics**

- particularly resistant to microorganisms (biostability)
- without boric acid, chlorine, phosphorus, sec. amines and formaldehyde
- high material compatibility
- low-foaming
- emulsion mixed with water gives good corrosion protection and increased pressure absorption capacity

## **Technical Product Data**

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C		1010	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 20 °C	mm²/s	65	DIN 51562-1

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen. 31.05.2023